

1/4" FLEXAIR hybrid polymer hose with pressed metal sleeves, non-scratch sheath and prevoS1 quick safety couplings



ID (in) 1/4"	Coupler ISI 06	Plug IRP 06	Length (ft) 25'
Operating pressure 29 to 174 psi	Temperature +5°F to +140°F	Construction PVC	Equipped with Coupler and adapter

Description				
Reference	ID (in)	Coupler	Plug	Length (ft)
RST RISB1425	1/4"	ISI 06	IRP 06	25'
RST RISB1450	1/4"	ISI 06	IRP 06	50'
RST RISB14100	1/4"	ISI 06	IRP 06	100'
RST RUSB1425	1/4"	USI 06	URP 06	25'
RST RUSB1450	1/4"	USI 06	URP 06	50'
RST RUSB14100	1/4"	USI 06	URP 06	100'
RST RESB1425	1/4"	ESI 07	ERP 07	25'
RST RESB1450	1/4"	ESI 07	ERP 07	50'
RST RESB14100	1/4"	ESI 07	ERP 07	100'

Reference	ID (in)	Coupler	Plug	Length (ft)
RST RASB1425	1/4"	ASI 06	ARP 06	25'
RST RASB1450	1/4"	ASI 06	ARP 06	50'
RST RASB14100	1/4"	ASI 06	ARP 06	100'

