

Regulator



Description					
Reference	Flow rate (l/min at 6 bar ?P	Operating pressure (bar)	NPT female thread	Flow rate (cfm at 90 psi ?P	Operating pressure (psi)
ATU R10100	1bar) = 750	Inlet: 0.8 - 15 Outlet: 0.5 - 10	1/8" FNPT	4 psi) = 26	Outlet : 12 to 220 Inlet : 10 to 145
ATU R10200	1bar) = 1 500	Inlet: 0.8 - 15 Outlet: 0.5 - 10	1/4" FNPT	4 psi) = 53	Outlet : 12 to 220 Inlet : 10 to 145
ATU R10101	1bar) = 4 300	Inlet: 0.8 - 15 Outlet: 0.5 - 10	3/8" FNPT	4 psi) = 150	Outlet : 12 to 220 Inlet : 10 to 145
ATU R10201	1bar) = 4 700	Inlet: 0.8 - 15 Outlet: 0.5 - 10	1/2" FNPT	4 psi) = 165	Outlet : 12 to 220 Inlet : 10 to 145
ATU R10102					

Reference	Flow rate (l/min at 6 bar ?P	Operating pressure (bar)	NPT female thread	Flow rate (cfm at 90 psi ?P	Operating pressure (psi)
ATU R10202					
ATU R10103					
ATU R10203					

