

Solid Band Stainless Steel Worm



Ø min./max. (in)

0.32 - 0.55

Tightening screw (lbf.ft)

1.8 - 2.6

Band width (in)

0.35

Construction

Stainless steel


Applications

Corrosive atmospheres


Description

Reference	Ø min./max. (in)	Tightening screw (lbf.ft)	Band width (in)
PBI9 814	0.32 - 0.55	1.8 - 2.6	0.35
PBI9 1117	0.43 - 0.67	1.8 - 2.6	0.35
PBI9 1320	0.51 - 0.79	2.2 - 3.0	0.35
PBI12 1524	0.59 - 0.95	3.0 - 3.3	0.47
PBI12 1928	0.75 - 1.10	3.0 - 3.3	0.47
PBI12 2232	0.87 - 1.26	3.0 - 3.3	0.47
PBI12 2638	1.02 - 1.50	3.0 - 3.3	0.47
PBI12 3244	1.26 - 1.73	3.7 - 4.4	0.47
PBI12 3850	1.50 - 1.97	3.7 - 4.4	0.47

Reference	Ø min./max. (in)	Tightening screw(lbf.ft)	Band width (in)
PBI12 4456	1.73 - 2.21	3.7 - 4.4	0.47
PBI12 5065	1.97 - 2.56	3.7 - 4.4	0.47
PBI12 5875	2.28 - 2.95	3.7 - 4.4	0.47
PBI12 6885	2.68 - 3.35	3.7 - 4.4	0.47
PBI12 7795	3.03 - 3.74	3.7 - 4.4	0.47
PBI12 87112	3.43 - 4.41	3.7 - 4.4	0.47
PBI12 104138	4.09 -5.43	3.7 - 4.4	0.47
PBI12 130165	5.12 - 6.50	3.7 - 4.4	0.47
PBI12 150180	5.91 - 7.09	3.7 - 4.4	0.47
PBI12 175205	6.89 - 8.07	3.7 - 4.4	0.47
PBI12 200231	7.87 - 9.09	3.7 - 4.4	0.47
PBI12 226256	8.89 - 10.08	3.7 - 4.4	0.47
PBI12 251282	9.88 - 11.10	3.7 - 4.4	0.47
PBI12 277307	10.91 - 12.09	3.7 - 4.4	0.47



7 mm



Dimensions

Reference	A inch
PBI9 814	0.787
PBI9 1117	0.787
PBI9 1320	0.787
PBI12 1524	0.866

Reference	A inch
PBI12 1928	0.906
PBI12 2232	0.984
PBI12 2638	0.984
PBI12 3244	1.142
PBI12 3850	1.142
PBI12 4456	1.142
PBI12 5065	1.26
PBI12 5875	1.26
PBI12 6885	1.26
PBI12 7795	1.26
PBI12 87112	1.26
PBI12 104138	1.26
PBI12 130165	1.26
PBI12 150180	1.26
PBI12 175205	1.26
PBI12 200231	1.26
PBI12 226256	1.26
PBI12 251282	1.26
PBI12 277307	1.26