Combination Micronic - Submicronic Filter - Regulator



Interchange
Industrial 1/4"

Inlet NPT female thread
1/2" FNPT

Outlet 1 coupling
ISI 06

Flow rate (cfm at 100 psi)
50

Operating pressure
29 to 174 psi

Temperature
+34°F to +150°F


Construction
Aluminum body and bowl

Equipped with
Quick release safety couplings and adaptors prevoS1

Description

Reference	Interchange	Inlet NPT female thread	Outlet 1 coupling	Flow rate (cfm at 100 psi)
MBR 203IS	Industrial 1/4"	1/2" FNPT	ISI 06	50
MBR 203US	Automotive 1/4"	1/2" FNPT	USI 06	50
MBR 203ES	High Flow 3/8"	1/2" FNPT	ESI 07	50

Prevost CORP - 74 Brookfield Oaks Drive, Ste. 3 - Greenville, SC 29607
Tel: +1 (800) 845-7220 - Email: sales.corp@prevostusa.com - www.prevostusa.com



Dimensions			
Reference	A inch	B inch	C inch
MBR 203IS	1.0269028871391	1.0826771653543	0.33464566929134
MBR 203US	1.0269028871391	1.0826771653543	0.33464566929134
MBR 203ES	1.0269028871391	1.0826771653543	0.33464566929134